



2684 Fenton Rd.
Ottawa, ON K1T3T7
Tel: 613.288.8490
Fax: 613.822.7093
Email: sales@walljuice.com
Web: www.walljuice.com

WALL PRINT INSTALLATION

INSTALLATION NOTES – READ THIS FIRST

1. Wall Print removable media is best suited for applications that require easy removal from smooth flat interior surfaces including painted dry walls that are smooth, clean and non-textured.
2. Always roll your Wall Print. NEVER fold or crease the material.
3. Roll up backing and keep in a clean safe place, if you plan to move your Wall Print in the future.
4. Wall Print must be at room temperature before printing and installation.
5. Surface must be cleaned prior to applying Wall Print. DO NOT USE SOAP OR ANY HOUSEHOLD CLEANING AGENTS. Surface must be completely dry before applying graphic.
6. For installation, you can use either a plastic squeegee or a clean, dry, unused paint roller to eliminate any air bubbles. Plastic squeegees are available for purchase from Wall Juice. NOTE: Always wrap a clean sock around the plastic squeegee to avoid abrasions on your print.
7. When installed properly, air bubbles should not occur. To remove air bubbles, begin at the center of the Wall Juice Print and push toward outside edges of the Wall Juice Print.
8. Painted walls should be allowed to dry 30 days prior to installation of Wall Prints.

INSTALLATION PROCESS TIPS

1. It is recommended that these steps are followed by 2 people for larger pieces.
2. Position your Wall Print in the desired location and hold in place with masking tape.
3. If your Wall Juice Print is taller than wider, begin peeling the backing from the top. If wider than taller, begin peeling from right to left.
4. Remove approximately 2 inches of backing with scissors. NOTE: do not cut the print – peel the backing and cut off 2 inches of the BACKING ONLY.
5. Apply the first two inches to the wall. Press the Print firmly against the wall to provide and use squeegee or paint roller to ensure firm contact between adhesive and wall.
6. While the first installer supports the print where the first 2 inches of adhesive have been applied to the wall, the second installer uses one hand to slowly remove the backing from behind, while using squeegee or paint roller to press on the front using a smooth back and forth motion – ensuring the entire print area and pressed firmly against the wall. The backing should be removed at the same pace as the application of pressure to the front.
7. Never allow the Wall Juice print to adhere to itself. If this does happen , do not panic, gently pull the two areas apart and re-apply.
8. If you notice air bubbles while applying, simply lift the print and reapply more carefully.
9. If you notice air bubbles after application is complete apply pressure with a squeegee beginning in the middle and pressing out towards the edges. Small air bubbles will often disappear within first 24 hours.